

## **WHAT IS CLAIMED IS:**

1. An installing device comprising:

a bar having a first threaded hole and two second threaded holes,  
the first threaded hole located between the two second threaded holes;

5           a first bolt movably extends through the first threaded hole and  
adapted to be in alignment with a hole in an object to be fitted with a bearing  
or sleeve, two second bolts threaded engaged with the second threaded holes,  
and

a carrying member having a first section and a second section  
10   which is co-axially connected to the first section, a diameter of the second  
section being larger than that of the first section, a stepped shoulder defined  
radially at a conjunction of the first section and the second section, a third  
threaded hole defined in an end surface of the first section, the carrying  
member and the bar being adapted to be located on opposite sides of the  
15   object having the hole, the first bolt adapted to extend through the hole in the  
object and threadedly engaged with the third threaded hole.

2. The device as claimed in claim 1, wherein the first threaded hole  
is located between the two second threaded holes.

3. The device as claimed in claim 1, wherein the first bolt and the  
20   two second bolts access to the bar from a first side of the bar, a second side  
of the bar adapted to contact a front side of the object.

4. The device as claimed in claim 1, wherein the first bolt accesses  
the bar from a first side of the bar and the two second bolts access the bar

from a second side of the bar, the first and the second sides being opposite from each other, the two second bolts each having a head which is adapted to contact at a front side of the object, the two nuts on the two second bolts contacting a second side of the bar.